

**Thermocouple**

	K type	E type	
Model	WRNT-01	WRET-01	
Temperature range	0~400°C		
Protective tube	Stainless steel Φ5mm		
Screw gauge	M12×1.5		
Material	Nickel Chromium-Nickel Silicon	Nickel Chromium-Constantan	

	K type	E type	
Model	WRNT-02	WRET-02	
Temperature range	0~400°C		
Protective tube	Stainless steel Φ6mm		
Screw gauge	M6×1.5		
Material	Nickel Chromium-Nickel Silicon	Nickel Chromium-Constantan	

	K type	E type	
Model	WRNT-03	WRET-03	
Temperature range	0~400°C		
Protective tube	Normal material Φ7mm or Stainless steel Φ7mm		
Screw gauge	M12×1		
Material	Nickel Chromium-Nickel Silicon	Nickel Chromium-Constantan	

	K type or J type		
Model	XL-102A		
Temperature range	0~400°C		
Protective tube	Stainless steel Φ5mm		
Screw gauge	M12×1		
Material	Nickel Chromium-Nickel Silicon		

	K type	E type	
Model	WRN-120	WRE-120	
Temperature range	0~1000°C		
Protective tube	Stainless steel Φ16mm		
Junction box	Splash proof		
Material	Nickel Chromium-Nickel Silicon	Nickel Chromium-Constantan	

	K type	E type	
Model	WRN-230	WRE-230	
Temperature range	0~1000°C		
Protective tube	Stainless steel Φ16mm		
Junction box	Water proof		
Screw gauge	M27×2		
Material	Nickel Chromium-Nickel Silicon	Nickel Chromium-Constantan	

**RTD**

	Cu50 type	Pt100 type	
Model	WZCT-03	WZPT-03	
Temperature range	0~400°C		
Protective tube	Normal material Φ7mm or Stainless steel Φ7mm		
Screw gauge	M12×1		