




Model and Description

HHC71C1(JQX-40)-30A-1C-12VDC



HHC71C2(JQX-40)-50A-1C-12VDC




★Contact form: A=NO, B=NC, C=NO&NC

Specification

Dimension		60mm*45mm*46mm	
Form	Rated load	30A	50A
	Max switching voltage	240VAC/28VDC	
Contact Feature	Contact resistance	≤100mΩ	
	Material	Silver Alloy	
	Electrical life	≥1*10 ⁵	
	Mechanical life	≥1*10 ⁷	
Operate voltage (23℃)		DC:≤75%*Rated voltage /	
Release voltage (23℃)		DC:≥10%*Rated voltage /	
Maximum voltage (23℃)		110%*Rated voltage	
Coil voltage	DC	DC6-220V(Customize allowed)	
	AC	/	
Coil power	DC	2.6W	
	AC	/	
Pick-up time		≤25ms	
Release time		≤15ms	
Dielectric strength	Between Same-pole contacts	1500VAC/1min(leakage current 1mA)	
	Between Opposite-pole contacts	/	
	Between contacts and coil	2500VAC/1min(leakage current 1mA)	
Insulation resistance		≥200mΩ(500VDC)	
Ambient temperature		-25℃ ~ 55℃	
Ambient humidity		45%-75%RH	
Atmospheric pressure		86-106KPa	
Shock resistance		10G (sinusoidal half-wave pulse: 11ms)	
Vibration resistance		10-55Hz (double amplitude: 1.5mm)	
Installation		Screw	
Packing	Inner box	Foam box	10PCS
	Outer box	Foam box	100PCS/CTN
	Dimension of the carton	100PCS/CTN	402mm*288mm*370mm
	Weight	1PCS 100PCS/CTN	Approximate 160g G.W:17Kg N.W:16Kg

Wiring Diagram & Bottom View



Performance Graph

